

DUAL CURTAIN CONTROLLER USER MANUAL



Introduction

Confio Dual Curtain Controller designed to control 2 Blinds. It works with motorized roller blinds, CT2CC is powered by a single-phase AC and provides precise positioning of blinds, so they can be set to the position you choose.

Technical Specifications

The specifications and permissible maximum Load ratings are tested at +25°C.

Power Input	240VAC, 50Hz
Maximum Load per Channel @240VAC	Inductive - Max 300W/Ch
Cumulative Load - 4 Channels Muxed @240VAC	NA
Operating Temperature	-10° to +55°C
Temperature Sensing	NA
Relative Humidity	8% - 80%RH

Dimensions	49mm x 49mm x 18mm
Radio Frequency	865.2MHz (IN)
Surge Protection	2kv
Typical Line of Sight Range	10~15m Indoor /30m Outdoor
Plastic Housing	Fire Retardant ABS
Supported Load Type	WT AC motors

Warnings & Considerations

CAUTION

READ INSTRUCTIONS IN FULL BEFORE USE

The Wiring Connection Diagram and Parameters to use are mentioned in the manual. The Manufacturer, Confio will not be held responsible for any loss or damage resulting from not following the instructions of the Operating Manual.

CAUTION

DO NOT CONNECT THE DEVICE TO LOADS EXCEEDING RECOMMENDED VALUES

Connect Loads to the module below the Load ratings to work normally. Do not connect overload, this may lead to module failure.

CAUTION

FOLLOW INSTRUCTION MANUAL FOR CIRCUIT CONNECTION

Connections must be made according to the instructions available on Operational Manual, faulty connection leads to manual failure.



DANGER

DANGER OF ELECTRIC SHOCK

All works on the Device may be performed only by a trained Installers. If the installation is done by an unauthorized Technician the Manufacturer will not be held responsible. Contact support@confioliabs.com or call +91-9606030659 for a list of authorized Technicians.



DANGER

DANGER OF ELECTRIC SHOCK

Any works introducing changes into the configuration of connections or the load must be always performed with disconnected voltage. Since there are high chances of voltage occurrence at the terminals even after Device turn off. (Turn off the MCB).



DANGER

DANGER OF ELECTRIC SHOCK


Faulty connection or use may result in fire or Electric Shock.

Safety Measures

- Before installation, make sure that the power supply mains is turned off.
- Remove the switchboard cover frame and the switch frame to access the switches.
- Select the Loads to be connected on particular Terminals.
- If multiple Loads are connected to a single terminal, use appropriate connectors to avoid short circuit.
- Use only minimum 1.5mm² wires and maximum 2.5mm² wires for connections.
- This Device requires a neutral lead to operate.

Circuit Connections

Follow the above Circuit Connection for connecting Curtain Controller Module. Check the Load capacity before connecting. Loads must not exceed the maximum capacity mentioned in the Instruction Manual.



NOTE: The Manufacturer, Confio will not be held responsible for any loss or damage resulting from not following the instructions of the Operating Manual.

Activating Dual Curtain Controller Module

1. Installing the Device

- Make sure that the power supply mains is turned off.
- Connect the device to the wiring diagram.
- Connect the line, neutral and the loads on Open, Close.
- Use only Bell Switches for SW1, SW2, SW3 and SW4.
- Complete all the connections and check the pairing before sealing the Electrical Box.

2. Managing the Device through Z-Wave Network

It is recommended to place the micro module within 3 meters Line of Sight, as adding mode requires direct communication with the Controller. Move the Module near to the Primary Controller during this step, if required.

Inclusion Methods

Method 1

Press the Node ID button (at the back of the Module), to start pairing the device to the Gateway.

Method 2

Toggle S1 3 times within 4 seconds to start pairing the device to the Gateway. (Sequence: ON-OFF ON-OFF ON-OFF).

Exclusion Methods

Method 1

Press the Node ID Button (at the back of the Module), to start the Exclusion process from the Gateway.

Method 2

Toggle S1 3 times within 4 seconds to start Unpairing the device from the Gateway. (Sequence: ON-OFF ON-OFF ON-OFF).

LED Indications

LED Indication	Status
Red Blinking	Excluded
Green Blinking	Included/Paired
Red and Green	In Pairing Mode

Operating the Dual Curtain Controller Module

The open-close functionality of the Controller Motor may be operated using the following options:

- Bell switches connected to S1 and S2, S3 and S4.
- Any Controller compatible with basic implementation of Z-Wave.
- Any Controller compatible with multi-channel implementation.
- Z-Wave compatible Android and iOS apps are available for Automation Gateway.

Additional Parameters		
Parameter 01	Curtain 1 Open Timer	
Range	4 Byte dec	Value duration
	1000	10Sec
	360000	1Hour
Default	6000 - 60Sec	
Description	This Parameter is designed Open Curtain 1 for a specific time	
Parameter 02	Curtain 1 Close Timer	
Range	4 Byte dec	Value duration
	1000	10Sec
	360000	1Hour
Default	6000 - 60Sec	
Description	This Parameter is designed Close Curtain 1 for a specific time	
Parameter 03	Curtain 2 Open Timer	
Range	4 Byte dec	Value duration
	1000	10Sec
	360000	1Hour
Default	6000 - 60Sec	
Description	This Parameter is designed Open Curtain 2 for a specific time	
Parameter 04	Curtain 2 Close Timer	
Range	4 Byte dec	Value duration
	1000	10Sec
	360000	1Hour
Default	6000 - 60Sec	
Description	This Parameter is designed Close Curtain 2 for a specific time	

4 - Byte Value	Duration
1500	15 s
3000	30 s
6000	1 min
30000	5 min
180000	30 min
360000	1 hour

Parameter 05	Onboard LED enable/disable
Range	0 to 1 (0: disable, 1: enable)
Default	1: enable

Description This Parameter enables or disables onboard LEDs

Common Issues

Pairing not Working: Confirm that the Gateway and the Curtain Controller are within 3 meters from each other while adding to the Gateway.

Resetting Device

For resetting the Micro Module, press and hold the Node ID button behind the Module for 10seconds. Then the Device will be restored to it's default settings.

Recommendations		
• If there are signs of water seeping into the Electrical Box, turn off the MCB and disconnect the power supply to avoid short circuits.		
• Check the space behind the Switch for placing the Curtain.		
• Turn off the MCB before installation of Curtain Module.		
• Use only minimum 1.5mm ² wires and maximum 2.5mm ² wires for connections.		
• Strictly follow the wiring diagram for connections.		
• Confirm that the open/close cables are marked correctly to fix them, if any issues arise in the motor in the future.		

Important Note

1. If there are signs of water seeping into the Electrical Box, turn off the MCB and disconnect the power supply to avoid short circuits.
2. Check the space behind the Switch for placing the Module.
3. Turn off the MCB before the installation of the Module.

Warranty

A Standard warranty of 24 months from the date of supply is applicable for all products

The warranty shall not cover:

- Mechanical damages caused by impact, falling or dropping the device or their object, unauthorized use or not observing the Operation Manual.
- Damages resulting from external causes, for example, flood, storm, fire, lightning, natural disasters.
- Damages resulting from surges in the power and/or telecommunication network, improper connection to the grid in a manner inconsistent with the operating manual, or from connecting other Devices not recommended by the Manufacturer.
- Damages resulting from the use of spurious spare parts or accessories improper for given model, repairing and introducing alterations by unauthorized persons.
- Defects caused by operating inoperable devices or accessories.

MEDHA
By Confio

For any technical and support queries,
please contact the Manufacturer

CONFIO TECHNOLOGIES PRIVATE LIMITED
#3500/A, 80 Feet Road,
Raghuvanahalli, Bangalore - 560062
Karnataka, India

Email: support@confiolabs.com
www.confiolabs.com